


Magnetic Measurements At ESRF

Loïc Lefebvre, Gaël Le Bec, Joël Chavanne, Christophe Penel, Eric Fene, Philippe Arnoux, Chamseddine Benabderrahmane, Grégory Giroud, Maxime Paulin, Franck Bidaut, Reine Verstreigen, Bertrand Cottin, Franck Revol

ESRF – The European Synchrotron, Grenoble, France

loic.lefebvre@esrf.fr

- **Context**
 - ESRF-EBS
 - Magnetic measurements benches
- **Magnetic Measurements**
 - Quadrupoles
 - Sextupoles
 - Permanent magnet dipoles
 - Dipole-quadrupoles
- **Fiducialization**
 - Issues and feedback





The ESRF designs a new generation of synchrotrons A new design for the storage ring

- 31 magnets + correctors

X32 cells

=> Low emittance – 4nm to < 140pm






The ESRF designs a new generation of synchrotrons
A new design for the storage ring

- 31 magnets + correctors

X32 cells


=> Low emittance – 4nm to < 140pm



No failure for IDM !!


- Check multipoles
- Shim the magnets (low gradient quadrupoles and sextupoles)
- Align the wire according to the magnet field for fiducialization

 **DANFYSIK**




High gradient quads

tesla
ENGINEERING LTD




High gradient quads, 2 stands

 **DANFYSIK**




Sextupoles

 **ESRF**
The European Synchrotron




Dipole modules

 **ESRF**
The European Synchrotron



Dipoles


tesla
ENGINEERING LTD



Dipole-quadrupoles


Quadrupole measurements

A Light For Science




• Harmonics


Multipole Analysis for High Gradient Quadrupole (Norm. @ Radius=7mm)




Multipole Analysis for Moderate Gradient Quadrupole (Norm. @ Radius = 13mm)



Integrated strength – QF6




Integrated strength – QF8



- Vertical position – shimmed quadrupoles

QF1 (65 magnets)




Average: -0.00641455 mm

Standard deviation: 0.0230001 mm

Average: $6 \mu\text{m}$

Std dev : $23 \mu\text{m}$

QD2 (228 magnets)




Average: -0.00271841 mm

Standard deviation: 0.0242653 mm

$-3 \mu\text{m}$

$24 \mu\text{m}$

QD3 (64 magnets)




Average: -0.00397082 mm

Standard deviation: 0.0211961 mm

$-4 \mu\text{m}$

$21 \mu\text{m}$

QF4E (35 magnets)



Average: -0.00202315 mm


Standard deviation: 0.0241109 mm

$-2 \mu\text{m}$

$24 \mu\text{m}$


Tolerances : $50 \mu\text{m}$ after shimming

- Roll Angle – shimmed quadrupoles



Tolerances: 130 μ rad after shimming


- Roll Angle – unshimmed quadrupoles




Bottom support were set according to a first magnetic measurement

Sextupole Measurements


A Light For Science




Multipole Analysis for Sextupoles (Norm. @ Radius=13mm)




Integrated strength – SF2



- Vertical position – shimmed sextupoles



- Roll Angle – shimmed sextupoles



Permanent Magnet Dipole



A Light For Science

Dipoles with longitudinal gradient

- 5 modules/DL: 5 field steps
- Length: 1.85 m
- 128 units (64 DL1, 64 DL2)
- PM material: $\text{Sm}_2\text{Co}_{17}$ ~ 12000 blocks
- Construction completed in September 2017



Movable flux shunt, fine adjustment




Passive temperature compensation, FeNi flux shunts : Temp. Coef < 20 ppm/C


Courtesy Joël Chavanne

Dipole-Quadrupole (DQ) field and gradient (Hall probe)

Gradient



Field




- Get the magnetic length
- Not precise enough to get all the multipoles

Courtesy Gaël Le Bec




Opening / Closing - dX deviation - SD1




dX – SD1 (mm)	
Min	-0.100
Max	0.143
Average	0.002
Std	0.033

Opening / Closing - dX deviation - SF2




dX – SF2 (mm)	
Min	-0.035
Max	0.098
Average	0.010
Std	0.021

Opening / Closing - dY deviation - SD1




dY – SD1 (mm)	
Min	-0.045
Max	0.130
Average	0.011
Std	0.026

Opening / Closing - dY deviation - SF2




dY – SF2 (mm)	
Min	-0.040
Max	0.058
Average	0.005
Std	0.017

Opening / Closing - dZ deviation - SD1




dZ – SD1 (mm)	
Min	-0.028
Max	0.013
Average	-0.001
Std	0.007

Opening / Closing - dZ deviation - SF2



dZ – SD1 (mm)	
Min	-0.021
Max	0.015
Average	0.000
Std	0.006



67 SD1 magnets were analysed for this study.
15 (22%) of the SD1 magnets have planimetric reassembly repeatability errors larger than 50µm.

46 SF2 magnets have been analysed for this study.
4 (9%) of the SF2 magnets have planimetric reassembly repeatability errors larger than 50µm.

47 QD3 magnets were analysed for this study.
No QD3 magnets have planimetric reassembly repeatability errors larger than 50µm.

- **Measurements**

- Automatic magnetic measurements – Manual fiducialization
- Magnetic measurements fit well the simulation
- Repeatability between mag. measurement at supplier premises and at the ESRF is quite accurate

- **Fiducialization**

- Issues with FARO/Romer Arm
- Must guarantee a good follow-up every week with a reference magnet
- Can reveal issues on the design – take time with technicians at each state (power supply, mechanical, vacuum...) to listen to their advices.

- **What we do next ?**

→ Bench installation, bug corrections

Measurement follow-up is quite challenging but once everything is settled we have now time to develop new tools and technics.

→ Sextupole correctors and refurbishment of IDs is the next step

THANK YOU FOR YOUR ATTENTION



IDM Group @ ski - 2018